

精锐
Elite

服务
Service

全球
Global



WhatsApp



微信/WeChat

**ONE STOP SERVICE FOR DESIGN
MANUFACTURING, AND SALES**
设计/制造/销售一站式服务



- 闸阀 Gate valve
- 截止阀 Globe valve
- 球阀 Ball valve
- 止回阀 Check valve
- 过滤器 Filter
- 水力阀 Hydraulic valve



电话Tel: (蒋)18006691180 / (王)15205878222

传真Fax: 0577-86890958

邮箱E-mail: vip@senli-valve.com

微信WeChat: 15205878222

Whatsapp/Skype: 18006691180

地址: 浙江省温州市龙湾区永兴街道滨海4道822号

Building 2, No.822, Binhai 4th Road, Yongxing Street, Longwan District, Wenzhou City, Zhejiang Province

www.sinli-valve.com

www.sinli-valve.com

COMPANY INTRODUCTION

公司简介



信利阀门有限公司是集设计、制造、销售为一体的阀门专业生产厂家。企业生产高品质阀门系列产品，以满足国内外用户对高技术阀门的需求。公司现生产国标、美标、德标、英标、日标以及各种非标定制产品，适用于石油、化工、电力、轻工，给排水等行业，畅销全世界，深受国内外用户的好评。公司拥有各类主要大中型精良的机械专用生产设备，配有现代化主要检验、检测设备。其主导产品有闸阀、截止阀、止回阀、球阀、过滤器等高、中、低压阀门、自控阀门及管道附件产品。

公称口径: DN15mm~DN1500mm;
公称压力: PN1.0MPa~42.0MPa(CLASS:150Lb~2500Lb);
工作温度: -196°C~680°C;
阀门主体材料主要有: WCB、CF8、CF8M、CF3、CF3M、2205、2507、904L、钛镍钨特殊合金等。

本公司始终重视人才的培养，经过多年的努力，已形成一种务实求是、追求完美的企业文化；拥有一批资深的技术、管理人才队伍；从接单、开发、设计、生产、服务一并作业完成；公司十分注重生产过程的质量控制，对从原材料供应商的审核、进料检验、生产线上产品筛检到最后成品检测都建立了完善而严格的质量保障体系。公司的质量方针是“客户满意，服务快捷，创新进取，持之以恒”；一贯以“质量求精、价格合理、信守合同”为经营理念，始终坚持顾客导向的宗旨；为广大客户提供优质的产品和满意的服务，愿我们携手共进，共创共赢！

Senli Valve Co., Ltd. is a professional valve manufacturer that integrates design, manufacturing, and sales. The enterprise produces high-quality valve series products to meet the needs of domestic and foreign users for high-tech valves. The company currently produces national, American, German, British, Japanese, and various non-standard customized products, suitable for industries such as petroleum, chemical, power, light industry, and water supply and drainage. They are popular worldwide and highly praised by domestic and foreign users. The company has various types of advanced mechanical production equipment, equipped with modern main inspection and testing equipment. Its leading products include gate valves, globe valves, check valves, ball valves, filters, High pressure and high temperature valves, Pressure self-sealing valves, low-temperature valves, and pipeline accessories.

Nominal diameter: DN15mm~DN1500mm;Nominal pressure: PN1.0MPa~42.0MPa (Class: 150Lb~2500Lb);Working temperature: -196°C~680°C;The main materials of the valve body include WCB, CF8, CF8M, CF3, CF3M, 2205, 2507, 904L, titanium nickel pickaxe special alloy, etc.

Our company has always attached great importance to talent cultivation, and after years of effort, we have formed a pragmatic and perfectionist corporate culture; Having a team of experienced technical and management talents; Complete tasks from receiving orders, development, design, production, and service simultaneously; The company attaches great importance to quality control in the production process, and has established a comprehensive and strict quality assurance system from auditing raw material suppliers, incoming inspection, product screening on the production line, to final product testing. The company's quality policy is "customer satisfaction, fast service, innovation and progress, and perseverance"; We always adhere to the business philosophy of "striving for excellence in quality, reasonable prices, and abiding by contracts", and always adhere to the customer-oriented principle; To provide our customers with high-quality products and satisfactory services, we hope to work together and create a win-win situation!

SENLI, is your always trustworthy partner

ENTERPRISE QUALIFICATION

企业资质



INTELLIGENT MANUFACTURING

智能智造



在激烈的市场竞争中
始终以诚信的经营、技术的创新、完善的售后为用户提供全方位服务，
让用户与我们紧密协作，共创美好未来！

In the fierce market competition,
we always provide users with a full range of services with honest management,
technological innovation, and perfect after-sales,
so that users can work closely with us to create a better future!





公称通径:
10mm~1000mm及1/2"~60".

工作压力:
1.0MPa~16.0MPa/150Lb~1500Lb/10K~160K.

工作温度:
-196°C~816°C.

采用标准: GB, DIN, API, ANSI, JIS, BS等.

产品材料:
WCB, A105, LCB, LF2, WC6, F11, WC9, CF8, F304, CF8M, F316, CF3, F304L, CF3M, F316L, CF8C, 4A, F51, 5A, F53, Inconel, Monel, 2205, 2507, 904L, 铜合金, 钛合金, 哈氏合金, 镍合金等.

驱动方式:
手动、蜗轮传动、伞齿轮、电动、气动、液动等.

Nominal diameter:
10mm to 1000mm and 1/2" to 60".

Working pressure:
1.0MPa~16.0MPa/150Lb~1500Lb/10K~160K.

Working temperature:
-196 °C to 816 °C.

Applicable standards:
GB, DIN, API, ANSI, JIS, BS, etc.

Product materials: WCB, A105, LCB, LF2, WC6, F11, WC9, CF8, F304, CF8M, F316, CF3, F304L, CF3M, F316L, CF8C, 4A, F51, 5A, F53, Inconel, Monel, 2205, 2507, 904L, copper alloy, titanium alloy, Hastelloy alloy, nickel alloy, etc.

Driving method:
Manual, worm gear transmission, bevel gear, electric, pneumatic, hydraulic, etc.

| | |
|---|--|
|  <p>美标法兰闸阀 150LB API Flanged Gate Valve</p> | |
|  <p>美标法兰闸阀 300LB API Flanged Gate Valve</p> |  <p>不锈钢美标闸阀 Stainless Steel Gate Valve</p> |
|  <p>美标不锈钢闸阀 API Stainless Steel Gate Valve</p> |  <p>高压法兰闸阀 900LB High Pressure Gate Valve</p> |
|  <p>伞齿轮闸阀 Worm Gear Gate Valve</p> |  <p>电动闸阀 Electric Gate Valve</p> |

| | | |
|---|---|--|
|  <p>不锈钢低温闸阀 Stainless Steel Low Temperature Gate Valve</p> |  <p>不锈钢低温闸阀 Low Temperature Gate Valve</p> |  <p>锻钢超低温法兰闸阀 Forged Steel Ultra-Low Temperature Gate Valve</p> |
|  <p>德标法兰闸阀 DIN Gate Valve</p> |  <p>国标法兰闸阀 GB Gate Valve</p> |  <p>暗杆闸阀 Non Rising Stem Gate Valve</p> |
|  <p>不锈钢软密封暗杆闸阀 Stainless Steel Soft Seal Concealed Stem Gate Valve</p> |  <p>锻钢闸阀 Forged Steel Gate Valve</p> |  <p>国标钛材闸阀 Titanium Gate Valve</p> |

GLOBE VALVE SERIES
截止阀系列

Nominal diameter:
10mm to 1000mm and 1/2" to 60".

Work pressure:
1.0MPa~16.0MPa/150Lb~1500Lb/10K~160K.

Working temperature:
-196 °C to 816 °C.

Applicable standards:
GB, DIN, API, ANSI, JIS, BS, etc.

Product materials:
WCB, A105, LCB, LF2, WC6, F11, WC9, CF8, F304, CF8M, F316, CF3, F304L, CF3M, F316L, CF8C, 4A, F51, 5A, F53, Inconel, Monel, 2205, 2507, 904L, copper alloy, titanium alloy, Hastelloy alloy, nickel alloy, etc.

Driving method:
Manual, worm gear transmission, bevel gear, electric, pneumatic, hydraulic, etc.

| | | |
|--|--|---|
|  美标截止阀 API Flanged Globe Valve |  美标截止阀 API Flanged Globe Valve |  不锈钢截止阀 Stainless Steel Flange Globe Valve |
|  双相钢截止阀 Duplex Steel Globe Valve |  国标碳钢截止阀 GB Cast Steel Globe Valve |  国标不锈钢截止阀 GB Stainless Steel Globe Valve |
|  不锈钢低温截止阀 Cryogenic Stainless Steel Globe Valve |  锻钢截止阀 Forged Steel Globe Valve |  904L国标法兰截止阀 GB Flanged Globe Valve |

Nominal diameter:
10mm to 1000mm and 1/2" to 60".

Work pressure:
1.0MPa~16.0MPa/150Lb~1500Lb/10K~160K.

Working temperature:
-196 °C to 816 °C.

Applicable standards:
GB, DIN, API, ANSI, JIS, BS, etc.

Product materials:
WCB, A105, LCB, LF2, WC6, F11, WC9, CF8, F304, CF8M, F316, CF3, F304L, CF3M, F316L, CF8C, 4A, F51, 5A, F53, Inconel, Monel, 2205, 2507, 904L, copper alloy, titanium alloy, Hastelloy alloy, nickel alloy, etc.

CHECK VALVE/FILTER SERIES
止回阀/过滤器系列

| | | |
|--|---|---|
|  美标旋启式止回阀 API Swing check valve |  美标钛材止回阀 Titanium Swing Check Valve | |
|  美标不锈钢止回阀 Stainless Steel Swing Check Valve |  国标不锈钢止回阀 GB Stainless Steel Swing Check Valve | |
|  旋启式止回阀 Swing check valve |  旋启式止回阀 Swing check valve |  Y型过滤器 Y-Type Strainer |

BALL VALVE SERIES
球阀系列

Nominal diameter:
10mm to 1000mm and 1/2" to 60".



Work pressure:
1.6MPa~10.0MPa/150Lb~1500Lb/10K~160K.

Working temperature:
-96 °C to 400 °C.

Applicable standards:
GB, DIN, API, ANSI, JIS, BS, etc.

Product materials:
WCB, A105, LCB, LF2, WC6, F11, WC9, CF8, F304, CF8M, F316, CF3, F304L, CF3M, F316L, CF8C, 4A, F51, 5A, F53, Inconel, Monel, 2205, 2507, 904L, copper alloy, titanium alloy, Hastelloy alloy, nickel alloy, etc.

Driving method:
Manual, worm gear transmission, electric, pneumatic, hydraulic, etc.

| | | | |
|--|---|--|---|
|  美标法兰球阀 API Flanged Ball Valve |  美标法兰球阀 API Flanged Ball Valve |  高平台球阀 High Platform Ball Valve |  高平台硬密封球阀 High Platform Hard Seal Ball Valve |
|  不锈钢法兰球阀 Stainless Steel Flanged Ball Valve |  国标法兰球阀 GB Flanged Ball Valve |  锻钢球阀 Forged Steel Flanged Ball Valve |  锻钢球阀 Forged Steel Flanged Ball Valve |
|  三片式锻钢高压球阀 3-PC Forged Steel High Pressure Ball Valve |  三片式锻钢焊接球阀 3-PC Forged Steel Welded Ball Valve |  二片式螺纹球阀 2-PC Threaded Ball Valve |  三片式球阀 3-PC Threaded Ball Valve |

HYDRAULIC VALVE SERIES
水力阀系列

| | | |
|--|---|---|
|  100X浮球阀 Float Ball Valve |  200X减压阀 Pressure-Reducing Valve |  500X持压泄压阀 Pressure Relief Valve |
|--|---|---|

COPPER VALVE SERIES
铜阀门系列

| | | |
|---|---|--|
|  闸阀 Gate Valve |  球阀 Ball Valve |  过滤器 Filter |
|---|---|--|